

ROTORS SPRAYS VALVES CONTROLLERS SENSORS CENTRAL CONTROLS MICRO

I-25

ultra

Hunter®





I-25 *Ultra* Performance Rotor More Distance, Larger Radius



Hunter I-25 *Ultra* rotors cover more distance and larger radius. Efficient, tough, and built to last.

I-25 *Ultra* Performance Rotor More Distance, Larger Radius

The I-25 *Ultra* gets the job done while keeping your wallet at ease. This rotor covers more distance, hitting a radius of 12.2 to 21.6 m. The compact and built-to-last construction comes with an optional stainless steel riser for tough-as-nails strength. With a 5-year warranty, the I-25 *Ultra* has options for reclaimed water ID and high-speed. A standard check valve is built in, and a wide selection of high performance nozzles are available.



Color-coded nozzles ensure full coverage performance.



Easy arc adjustment right from the top.



Proven and tested water-lubricated gear drive system.



Reclaimed option available.



The perfect rotor for commercial and recreational sites.

EASY IDENTIFICATION

Nozzles are color-coded. Each standard nozzle has a number engraved on the outer surface. The numbers tell you the approximate nozzle flowrate.

TWO NOZZLES IN ONE UNIT. CHANGING BOTH IS A SNAP.

We've combined two different nozzles, each with its own function, in one color-coded single unit. Replace both nozzles with one simple modification. Just snap one out, snap another in, and both primary and secondary nozzles are changed.

CHOICE. VERSATILITY.

PERFORMANCE.

12 different nozzles handle any radius from 12.2 m to 21.6 m plus any flow rate from 14.4 to 119 l/min (0.86 to 7.15 m³/hr). More choices to meet your specific needs.



ULTRA

Easy arc adjustment (50° - 360°): Up, down, wet or dry with through-the-top convenience, non-reversing.

ULTRA

Automatic arc return: returns to the original arc regardless of where the turret is turned.

ULTRA

Non-strippable, vandal-proof drive mechanism enables the turret to be turned without causing damage.

100% Adjustable: Full and part circle operation in a single rotor.

Available in plastic or stainless steel riser.

Available in 4" or 6" pop up.

Hunter[®]

ultra

Charts and Specs

I-25 Ultra Nozzle Performance Data – Metric

Nozzle	Pressure		Radius		Flow		Precip mm/hr	
	Bars	KPa	m	m ² /hr	l/min	■	▲	
4 Yellow	2.5	248	11.9	0.82	13.6	12	13	
	3.0	303	12.2	0.91	15.2	12	14	
	3.5	352	12.5	0.98	16.4	13	15	
	4.0	400	12.5	1.05	17.5	13	16	
	4.5	448	12.8	1.11	18.6	14	16	
5 White	2.5	248	11.9	0.82	13.6	12	13	
	3.0	303	12.2	0.91	15.2	12	14	
	3.5	352	12.5	0.98	16.4	13	15	
	4.0	400	12.5	1.05	17.5	13	16	
	4.5	448	12.8	1.11	18.6	14	16	
7 Orange*	2.5	248	11.9	0.82	13.6	12	13	
	3.0	303	12.2	0.91	15.2	12	14	
	3.5	352	12.5	0.98	16.4	13	15	
	4.0	400	12.5	1.05	17.5	13	16	
	4.5	448	12.8	1.11	18.6	14	16	
8 Lt. Brown	2.5	248	11.9	0.82	13.6	12	13	
	3.0	303	12.2	0.91	15.2	12	14	
	3.5	352	12.5	0.98	16.4	13	15	
	4.0	400	12.5	1.05	17.5	13	16	
	4.5	448	12.8	1.11	18.6	14	16	
10 Lt. Green*	2.5	248	11.9	0.82	13.6	12	13	
	3.0	303	12.2	0.91	15.2	12	14	
	3.5	352	12.5	0.98	16.4	13	15	
	4.0	400	12.5	1.05	17.5	13	16	
	4.5	448	12.8	1.11	18.6	14	16	
13 Lt. Blue	2.5	248	11.9	0.82	13.6	12	13	
	3.0	303	12.2	0.91	15.2	12	14	
	3.5	352	12.5	0.98	16.4	13	15	
	4.0	400	12.5	1.05	17.5	13	16	
	4.5	448	12.8	1.11	18.6	14	16	
15 Gray*	2.5	248	11.9	0.82	13.6	12	13	
	3.0	303	12.2	0.91	15.2	12	14	
	3.5	352	12.5	0.98	16.4	13	15	
	4.0	400	12.5	1.05	17.5	13	16	
	4.5	448	12.8	1.11	18.6	14	16	
18 Red	2.5	248	11.9	0.82	13.6	12	13	
	3.0	303	12.2	0.91	15.2	12	14	
	3.5	352	12.5	0.98	16.4	13	15	
	4.0	400	12.5	1.05	17.5	13	16	
	4.5	448	12.8	1.11	18.6	14	16	
20 Dk. Brown*	2.5	248	11.9	0.82	13.6	12	13	
	3.0	303	12.2	0.91	15.2	12	14	
	3.5	352	12.5	0.98	16.4	13	15	
	4.0	400	12.5	1.05	17.5	13	16	
	4.5	448	12.8	1.11	18.6	14	16	
23 Dk. Green	2.5	248	11.9	0.82	13.6	12	13	
	3.0	303	12.2	0.91	15.2	12	14	
	3.5	352	12.5	0.98	16.4	13	15	
	4.0	400	12.5	1.05	17.5	13	16	
	4.5	448	12.8	1.11	18.6	14	16	
25 Dk. Blue*	2.5	248	11.9	0.82	13.6	12	13	
	3.0	303	12.2	0.91	15.2	12	14	
	3.5	352	12.5	0.98	16.4	13	15	
	4.0	400	12.5	1.05	17.5	13	16	
	4.5	448	12.8	1.11	18.6	14	16	
28 Black	2.5	248	11.9	0.82	13.6	12	13	
	3.0	303	12.2	0.91	15.2	12	14	
	3.5	352	12.5	0.98	16.4	13	15	
	4.0	400	12.5	1.05	17.5	13	16	
	4.5	448	12.8	1.11	18.6	14	16	

I-31 Ultra High-Speed Nozzle Performance Data – Metric

Nozzle	Pressure		Radius		Flow		Precip mm/hr	
	Bars	KPa	m	m ² /hr	l/min	■	▲	
4 Yellow	2.5	248	11.0	0.81	13.6	14	16	
	3.0	303	11.3	0.91	15.1	14	16	
	3.5	352	11.6	0.99	16.4	15	17	
	4.0	400	11.6	1.06	17.6	16	18	
	4.5	448	11.6	1.13	18.8	17	19	
5 White	2.5	248	11.3	0.93	15.5	15	17	
	3.0	303	11.6	1.04	17.3	16	18	
	3.5	352	11.9	1.13	18.9	16	18	
	4.0	400	12.2	1.22	20.3	16	19	
	4.5	448	12.2	1.30	21.6	17	20	
7 Orange*	2.5	248	11.9	1.32	22.9	18	22	
	3.0	303	12.2	1.46	24.3	20	23	
	3.5	352	12.5	1.57	26.2	20	23	
	4.0	400	12.8	1.68	27.9	20	24	
	4.5	448	13.1	1.78	29.6	21	24	
8 Lt. Brown	2.5	248	12.5	1.54	25.7	20	23	
	3.0	303	12.8	1.72	28.6	21	24	
	3.5	352	13.1	1.86	31.0	22	25	
	4.0	400	13.4	2.00	33.3	22	26	
	4.5	448	13.4	2.13	35.4	24	27	
10 Lt. Green*	2.5	248	13.7	2.15	35.8	23	26	
	3.0	303	14.3	2.38	39.6	23	27	
	3.5	352	14.0	2.32	38.6	24	27	
	4.0	400	14.3	2.48	41.3	24	28	
	4.5	448	14.6	2.63	43.9	25	28	
13 Lt. Blue	2.5	248	14.9	2.75	45.7	25	28	
	3.0	303	15.5	3.07	51.2	25	29	
	3.5	352	15.5	3.24	54.0	27	31	
	4.0	400	14.6	2.57	42.8	24	28	
	4.5	448	15.2	2.91	48.5	25	29	
15 Gray*	2.5	248	15.5	3.24	54.0	27	31	
	3.0	303	14.6	2.86	47.7	27	31	
	3.5	352	14.9	3.05	50.8	27	32	
	4.0	400	15.2	3.22	53.7	28	32	
	4.5	448	15.5	3.38	56.3	28	32	
18 Red	2.5	248	16.2	3.53	58.8	27	31	
	3.0	303	14.9	3.08	51.4	28	32	
	3.5	352	15.2	3.31	55.2	29	33	
	4.0	400	15.5	3.52	58.7	29	34	
	4.5	448	16.2	3.72	62.0	29	33	
20 Dk. Brown*	2.5	248	16.8	3.91	65.2	28	32	
	3.0	303	17.4	4.11	68.5	27	31	
	4.0	400	16.2	3.97	66.2	30	35	
	4.5	448	16.5	4.20	70.1	31	36	
	5.0	496	17.1	4.42	73.7	30	35	
23 Dk. Green	2.5	248	17.7	4.66	77.7	25	28	
	3.0	303	17.7	4.86	81.0	31	36	
	3.5	352	18.0	5.05	84.2	31	36	
	4.0	400	17.1	4.88	81.3	33	39	
	4.5	448	17.4	5.18	86.3	34	40	
25 Dk. Blue*	2.5	248	17.7	4.66	77.7	25	28	
	3.0	303	18.3	6.04	100.6	36	42	
	3.5	352	18.3	6.29	104.8	36	42	
	4.0	400	17.7	5.23	87.1	33	39	
	4.5	448	18.3	5.58	93.1	33	39	
28 Black	2.5	248	18.9	6.52	108.6	37	43	
	3.0	303	18.9	6.52	108.6	36	42	
	3.5	352	19.5	6.77	112.8	36	41	
	4.0	400	18.9	7.01	116.9	36	41	
	4.5	448	19.8	7.24	120.7	35	40	

* 5 standard nozzles included with each sprinkler.
Note: All precipitation rates are calculated for 180-degree operation.
 For the precipitation rate for a 360-degree sprinkler, divide by 2.

SPECIFICATIONBUILDER

MODEL	FEATURES	OPTIONS
I-25-04 = 4" Pop-up	XX, XX-R, SS, SS-R, SS-HS, SS-HS-R	04-28 = Factory installed nozzle B = BSP Inlet
I-25-06 = 6" Pop-up	SS	25 *Nozzle pack is supplied installed nozzle has be

EXAMPLE ▶ I-25-06 - SS - 25

KEY TO FEATURES:
 XX = Adjustable arc, 50-360 degrees, plastic riser, with Check Valve
 XX-R = Adjustable arc, 50-360 degrees, plastic riser, with Check Valve and reclaimed water ID
 SS = Adjustable arc, 50-360 degrees, stainless riser, with Check Valve
 SS-R = Adjustable arc, 50-360 degrees, stainless riser, with Check Valve and reclaimed water ID
 SS-HS = High Speed, ADJ arc, 50-360 degrees, stainless riser, with Check Valve
 SS-HS-R = High Speed, ADJ arc, 50-360 degrees, stainless riser, with Check Valve and reclaimed water ID