

PRS40

APPLICATION
Residential/Commercial

MODELS
Shrub, 4", 6", 12"

PRS40 IS DESIGNED FOR OPTIMAL PERFORMANCE AT 40 PSI WHEN PAIRED WITH THE REVOLUTIONARY MP ROTATOR.

FEATURES

- Application: Residential/commercial
- Models: Shrub, 4", 6", 12"
- No side inlet (NSI) version available in 6" and 12"
- Warranty period: 5 years

ADVANCED FEATURES

- Identification cap is gray for easy field ID
- Pressure regulated to 40 PSI
- Co-molded wiper seal with UV resistant material
- Drain check valve (up to 14' of elevation)
- Body cap won't leak under high pressure

- Heavy-duty retraction spring
- Innovative directional flush plug design
- Reclaimed purple body cap (optional)
- Compatible with all female threaded nozzles

OPERATING SPECIFICATIONS

Recommended pressure range: 15 to 100 PSI

FACTORY INSTALLED OPTIONS

Reclaimed water ID cap

USER INSTALLED OPTIONS

Reclaimed water ID cap (P/N 458530)

Snap-on reclaimed cover (P/N PROSRCCAP)

PRS40 formerly MPR40



PRESSURE
REGULATED AT
40 PSI



PROS-00-PRS40:
Inlet size: 1/2" Female NPT



PROS-04-PRS40:
Overall height: 5 1/8"
Exposed diameter: 2 1/4"
Inlet size: 1/2" Female NPT



PROS-06-PRS40-CV: Overall height: 8 3/4"
Exposed diameter: 2 1/4"
Inlet size: 1/2" Female NPT



PROS-12-PRS40-CV:
Overall height: 16 1/8"
Exposed diameter: 2 1/4"
Inlet size: 1/2" Female NPT



DESIGNED SPECIFICALLY FOR MP ROTATOR

SPECIFICATIONBUILDER

www.hunterindustries.com/PRS40

PRS40 MODELS (formerly MPR40)	OPTIONS
PROS-00-PRS40 = 40 PSI regulated shrub adapter	(blank) = No option
PROS-04-PRS40-CV = 40 PSI regulated 4" pop-up	R = Factory-installed reclaimed body cap (shrub molded in purple)
PROS-06-PRS40-CV = 40 PSI regulated 6" pop-up	
PROS-12-PRS40-CV = 40 PSI regulated 12" pop-up	6" and 12" models will come as no side inlet

EXAMPLES

PROS-04-PRS40-CV	4" pop-up regulated at 40 PSI, and drain check valve
PROS-06-PRS40-CV	6" pop-up regulated at 40 PSI, and drain check valve
PROS-12-PRS40-CV - R	12" pop-up regulated at 40 PSI, drain check valve, and reclaimed body cap